


MOON!

5302 - LAMP H.16 IN.
DESIGN BY TRISTAN LOHNER

RESIDENTIAL CONTRACT INTENSIVE



Aluminum frame
Polyethylene diffuser
Lighting intensity : 2 warm white (100% & 50%) + 2 cool white (100% & 50%) + OFF
T° color : 1 warm white (3000°K) and 1 cool white (6000°K)
Technology LED - 2.5 W
Luminous flux : 150 lm
Min. Battery life : 8 h - Max. : 16 h
Rechargeable (7h)
Type of power supply : USB - Cable (supplied) 78 in.
Controlled with switch
Bypass to prevent battery damage during wired use
IP44 (ingress protection) | IK10 (impact resistance) | CE | FCC
Powered by Smart & Green



1,6 lb


530282 ● Cactus
530273 ● Honey
530214 ● Nutmeg

530247 ● Anthracite
530221 ● Acapulco Blue
530220 ● Red Ochre

NEW
NEW
NEW

5320 - LAMP H.25 IN.
DESIGN BY TRISTAN LOHNER

NEW RESIDENTIAL CONTRACT INTENSIVE



Aluminum frame
Polyethylene diffuser
Lighting intensity : 2 warm white (100% & 50%) + 2 cool white (100% & 50%) + OFF
T° color : 1 warm white (3000°K) and 1 cool white (6000°K)
Technology LED - 7 W
Luminous flux : 500 lm
Min. Battery life : 7 h - Max. : 13 h
Rechargeable (4h)
Type of power supply : ABS plastic charging base & transformer
110-230 Apv*/24 Dpv** IPX0 Multi-type sockets - Cable (supplied) 59 in.
Touch-activated light or remotely using the integrated Bluetooth system compatible with the «Fermob Lighting» app
Bypass to prevent battery damage during wired use
IP44 (ingress protection) | IK10 (impact resistance) | CE | FCC
Powered by Smart & Green



5,7 lb

532082 ● Cactus
532047 ● Anthracite

NEW

532021 ● Acapulco Blue
532020 ● Red Ochre

NEW
NEW

MOON!

5310 - LAMP H.53 IN.
DESIGN BY TRISTAN LOHNER



Aluminum frame
Polyethylene diffuser
Lighting intensity : 2 warm white (100% & 50%) + 2 cool white (100% & 50%) + OFF
T° color : 1 warm white (3000°K) and cool white (6000°K)
Technology LED - 7 W
Luminous flux : 500 lm
Min. Battery life : 7 h - Max. : 13 h
Rechargeable (4h)
Type of power supply : ABS plastic charging base & transformer
110-230 Apv*/24 Dpv** IPX0 Multi-type sockets - Cable (supplied) 59 in.
Touch-activated light or remotely using the integrated Bluetooth system
compatible with the «Fermob Lighting» app
Bypass to prevent battery damage during wired use
IP44 (ingress protection) | IK10 (impact resistance) | CE | FCC
Powered by Smart & Green

531082	Cactus		531021	Acapulco Blue	NEW
531047	Anthracite	NEW	531020	Red Ochre	NEW

* Alternating power volt / **Direct power volt